

Appl. No 10/700,432

Amdt. Dated 11/17/2005

Reply to Office action of 09/21/2005

5

Amendments to the Specification:

Please replace the specification with the following amended specification:

Field of the Invention

10

The present invention relates to a suspension structure for a front wheel assembly of a wheelchair, and more particularly to a suspension structure for a front wheel assembly of a wheelchair that is capable of saving production cost with its simple structure as well as reducing the kinetic energy dissipation to the least.

15

Description of the Prior Arts

20

Referring to Fig. 1, a conventional suspension structure of a wheelchair generally includes a frame 10 provided with a driving wheel 11 at both sides thereof respectively, ~~both of the driving wheels 11 are~~ and the driving wheel 11 is driven by a motor 12, ~~at both sides~~ . At either side of the frame 10 is further defined [with] an ear member 13 ~~respectively and each of which~~ that is pivotally connected with a first connecting rod 14 ~~correspondingly. The connecting rods 14 each~~ rod 14 has an end connected [with] to the motor 12 and has another end protruded ahead of the frame 10.

Furthermore, a mounting bracket 15 is defined at both sides of the front end of the frame 10 respectively and at the end of [each] the mounting bracket 15 is ~~disposed with~~ installed a jockey wheel 16. A side of [each] the mounting bracket 15 is connected ~~with that of~~ to the front end of the connecting rod 14
5 by ~~virtue of~~ a connecting plate 17, furthermore, a plurality of rollers 171 are ~~roller 171~~ is disposed in the connecting plate 17, so as to allow the mounting bracket 15 to rotate relative to the connecting rod 14, ~~and vice versa.~~

By such arrangements, the mounting ~~brackets 15 are~~ bracket 15 is able to rotate upward when the jockey wheels 16 are traversing a ~~curb or other~~
10 ~~upstanding obstacle~~, and the connecting rod 14 will ~~be driven to~~ rotate downward by virtue of the connecting plate 17 ~~as well as the roller~~ and the rollers 171, so as to increase. Therefore, the load on the driving wheels 11 and ~~thus increase~~ the friction of the driving wheels 11 with respect to the road will be increased. [By] In this way, the driving wheels 11 ~~are able~~ can get enough
15 force to push the jockey wheels 16 ~~by force to climb~~ over the [curb] obstacle. However, ~~there are some disadvantages of this~~ conventional suspension structure for a jockey wheel of wheelchair still has some defects that need to be improved ~~as follows:~~

First, upon encountering an obstacle ~~a curb~~, the connecting rod 14
20 will actuate ~~so as to increase the load on the driving wheels 11 and thus, so as~~ to make the driving wheels 11 ~~are able to~~ push the jockey wheels 16 ~~to~~ traverse over the obstacle ~~by force. Thereby .~~ However, this method of traversing the obstacle curb will [cost a great kinetic] consume a lot of energy

of the motor 12, ~~viz. a great dissipation of electrical energy.~~

Second, the structure conventional front wheel suspension is too complicated since the driving wheels 11 and the mounting brackets 15 need to be provided with connecting plates 17 as well as the connecting rods 14 and the connecting plate 17 must be connected to the driving wheels 11 and to the mounting bracket 15, respectively, and the connecting plate 17 has to be equipped with rollers 171, it is not only complicated in structure but also will increase the production cost.

The present invention has arisen to mitigate and/or obviate the afore-described disadvantages of the conventional suspension structure for front wheel assembly of a wheelchair.

SUMMARY OF THE INVENTION

The primary object of the present invention is to provide a suspension structure that has front wheel assemblies disposed at corresponding brackets of a frame of wheelchair, wherein the front wheel assemblies will rotate upward about the corresponding jockey wheels upon encountering a curb or other obstacle of the like, [such] this will effect [effects] an uplift of the front end of the frame of wheelchair, and meanwhile the gravity center of the user ~~as well as~~ and the frame of the wheelchair will move backward, so as to reduce the load on the jockey wheels, by this way, the jockey wheels of the wheelchair are able to climb over the curb without difficulties. Since the ~~conventional~~ wheelchair traverses the curb through the movement of the user's gravity center, this method enables the wheelchair of the present

invention to traverse the curb with the least kinetic energy.

Another object of the present invention is to provide a suspension structure for a front wheel assembly of a wheelchair, which is capable of traversing a curb or other obstacle of the like without difficulties, furthermore,
5 it is ~~simple~~ simply structured relative to conventional wheelchair so as not only to facilitate the assembly but reduce the production cost as well.

The present invention will become more obvious from the following description when taken in connection with the accompanying drawings, which shows, for purpose of illustrations only, the preferred embodiments in
10 accordance with the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a side view of a conventional suspension structure for a front wheel assembly of a wheelchair;

Fig. 2 is a perspective assembly view of a suspension structure for a
15 front wheel assembly of a wheelchair in accordance with the present invention;

Fig. 3 is an exploded view of the suspension structure for a front wheel assembly of a wheelchair in accordance with the present invention;

Fig. 4 is an illustrative view of showing the performance of
20 suspension structure of the present invention for a front wheel assembly of a wheelchair upon encountering a curb;

Fig. 5 is another illustrative view of showing the performance of suspension structure of the present invention for a front wheel assembly of a

wheelchair upon encountering a curb;

Fig. 6 is a third illustrative view of showing the performance of suspension structure of the present invention for a front wheel assembly of a wheelchair upon encountering a curb;

5 Fig. 7 is a fourth illustrative view of showing the performance of suspension structure of the present invention for a front wheel assembly of a wheelchair upon encountering a curb;

10 Fig. 8 is an exploded view of the suspension structure for a front wheel assembly of a wheelchair in accordance with another embodiment of the present invention;

Fig. 9 is a plan assembly view of Fig. 8;

Fig. 10 is another plan assembly view of Fig. 8.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Referring to Figs. 2-3, ~~wherein~~ which show a preferred embodiment of the present invention, in which, a pair of front wheel assemblies 30 is installed on a frame 20 of a wheelchair by virtue of positioning bolts 40, on ~~both sides~~ each side of the frame 20 is ~~provided with~~ installed a driving wheel 21 ~~respectively and each of which is driven by~~ , and a motor 22 is used to rotate the driving wheel 21.

20 The frame 20 is provided at either side thereof with a mounting bracket 23 ~~at both sides respectively, on each of which~~ in the mounting bracket 23 is defined [with] a pair of holes 24 and [at] in the bottom of the [same] mounting bracket 23 is formed a slot 25 ~~is formed~~. The driving wheels

21 are located at the rear portion of the frame 20.

Each of the front wheel assemblies 30 includes a jockey wheel 33 disposed at the front end of a strut 31 by virtue of a pedestal 32. At both sides of the rear end of [each] the strut 31 ~~thereof an~~ is formed two opposite holes
5 34 ~~is defined respectively with corresponding~~ to be aligned to the holes 24 [on] in the mounting brackets 23 of the frame 20. A bolt 35 is applied to insert in the holes 24 of each mounting bracket 23 and those holes 34 of the corresponding strut 31. [At] In the bottom of the rear end of [each] the strut 31 is formed a slot 36 ~~is defined with corresponding~~ that is to be aligned to the
10 slot 25 in the ~~corresponding~~ mounting bracket 23 of the frame 20, and in the ~~alike, at top surface of the [same]~~ strut 31 is formed [with] a locating hole 37 ~~with corresponding aligned~~ aligned to the slot 36 ~~at the bottom~~.

The positioning bolts 40 ~~serve to insert~~ each is inserted in the locating [holes] hole 37 and the slot 36 of the ~~corresponding~~ front wheel assembly 30
15 ~~as well as~~ and the slot 25 [on] of the mounting bracket 23 of the frame 20. A rubber ring 41 is mounted onto the positioning bolt 40 and located between the mounting bracket 23 of the frame 20 and the strut 31 of the front wheel assembly 30, ~~still~~. And on the positioning bolt 40 is further mounted another rubber ring 42 ~~is mounted and~~ located above the locating hole 37 of the
20 ~~corresponding~~ front wheel assembly 30.

Referring to Figs. 4-7, when the wheelchair runs on [the] a smooth road, the weight of the user and the wheelchair will be equally loaded on the two driving wheels 21 ~~as well as~~ and the jockey wheels 33 of the front wheel

assemblies 30. However, the jockey wheels 33 of the front wheel assemblies 30 will be stopped at a very beginning of stop rotating once encountering an a ~~curb or other upstanding~~ obstacle. ~~However~~At the moment, the two driving wheels 21 [are] will keep rotating forward, thus ~~the jockey wheels 33 work as~~
5 ~~a fulcrum and~~ the strut 31 of [each] the front wheel assembly 30 will rotate about [it] upwardly around the jockey wheel 33. Since the strut 31 of [each] the front wheel assembly 30 is disposed on the mounting bracket 23 of the frame 20, the upward rotation of the strut 31 of the front wheel assembly 30 will cause an upward movement of the front end of the frame 20 (as shown in
10 Fig. 5). After the ~~upward movement of the~~ front end of the frame 20 moves upward, the frame 20 will tilt backward. ~~And, and~~ the user will tilt backward along with the frame 20. It will be noted that, at [the] this moment, the gravity center of the user ~~as well as~~ and that of the frame 20 will load on the paired driving wheels 21, such that the weight on the jockey wheel 33 of [each] the
15 front wheel assembly 30 is lightened. ~~By this way~~ Therefore, the jockey wheel 33 of [each] the front wheel assembly 30 [may] can traverse the ~~curb or the like~~ obstacle without difficulty [cause] because it is driven by the forward rotation of the ~~driving~~ jockey wheel 33 of the ~~respective~~ front wheel assembly 30 (as shown in Fig. 6). After the jockey wheel 33 of [each] the front wheel
20 assembly 30 ~~climbed~~ climbs over the obstacle [curb], the weight of the user and the frame 20 will move forward, so as to increase the load on the mounting brackets 23 of the frame 20. At the same time, the rubber ring 42 above the locating hole 37 of the strut 31 can alleviate the shock caused by an

increased load on the mounting brackets 23 of the frame 20. It will be noted that the rubber ring 42 is not a necessary element, ~~which just~~ it only plays a role of ~~comforting the riding in traversing a curb or the like~~ a buffer (as shown in Fig. 7).

5 Thereby, according to the present invention, when the jockey wheel 33 of [each] the front wheel assembly 30 ~~encounters an~~ approaches a curb or ~~other upstanding~~ obstacle, the strut 31 of the front wheel assembly 30 will [upward] rotate upwardly about the ~~corresponding~~ jockey wheel 33 and this will cause an upward movement of the front end of the frame 20[, at]. At the
10 same time, the gravity of the user as well as the frame 20 will move backward so as to alleviate the load on the jockey wheel 33 ~~of the front wheel assembly 30, such that enables~~ thus enabling the jockey wheel 33 of the front wheel assembly 30 to traverse the obstacle more [curb] easily. In other words, ~~in terms of design, the method of traversing a curb in accordance with the~~
15 ~~present invention by taking advantage of the movement of the gravity center of the user that is different from that of~~ unlike the conventional wheelchair [by] that overcomes the obstacle totally relying on the strong propulsion of the driving wheels 21, the wheelchair of the present invention can traverse the obstacle more easily by shifting the gravity center of the user. The movement
20 of the gravity center of the user ~~may cause an alleviation of~~ can reduce the load on the front wheel assembly 30, so as to enable the driving wheels 21 to move forward ~~on as well as~~ , thus reducing kinetic the energy dissipation of the driving wheels 21.

~~In addition, the structure of the present invention is rather simple as only having the strut 31 of the front wheel assembly 30 disposed on mounting bracket 23 of the frame 20 which is simple structured relative to conventional wheelchair so as not only to facilitate the assembly but reduce the production~~
5 ~~cost as well.~~

Referring to Figs. 8-9, which ~~shows~~ show a suspension structure of a front wheel assembly of a wheelchair in accordance with another embodiment of the present invention, wherein the positioning bolt 40 can be inserted upward through the slot 25 of the mounting bracket 23, the rubber ring 41, the
10 ~~positioning~~ locating holes 37, the slot 36 of the front wheel assembly 30 and the rubber ring 42 respectively, and then a sleeve 43 is mounted onto the top end of the positioning bolt 40 and finally locked by an adjusting screw nut 44. By such a manner, the length of the positioning bolt 40 may be adjusted by
15 ~~adjustment of rotating~~ the adjusting screw nut 44. The sleeve 42 of the positioning bolt 40 is moved by rotating the adjusting screw nut 44, such that the user is able to adjust the elastic force of the rubber rings 41, 42 of the positioning bolt 40 on the basis of his/her own weight. For instance, for a heavy weight user, he/she may unloose the adjusting screw nut 44 moderately so as to lengthen the operation range of the positioning bolt 40 (the rubber
20 rings are under a light pressure), vice versa, the light weight user may shorten the operation range of the positioning bolt 40 [same], so as to make the riding comfortable.

Referring to Fig. 10, wherein the positioning bolt 40 can be provided

at the external periphery thereof with a spring 45, so as to prevent the strut 31 of the front wheel assembly from swaying up and down when moving the wheelchair, furthermore, it is able to increase the elastic force of the rubber ring 41.

5 While we have shown and described various embodiments in accordance with the present invention, it should be clear to those skilled in the art that further embodiments may be made without departing from the scope of the present invention.